



適用機械種類

APPLICATION

- 線切割機

- Wire cutting machine

特性及功能

FEATURE

- 採上吹式散熱，可完全將熱氣排出，不影響周圍溫度。
- 採用恆溫控制，可確保模具加工精度，減少銅線消耗。
- 採用智慧型溫度控制器，精度 0.5°C~1°C。
- 採機體同溫控制，感溫器可外拉，安裝於機器床台。
- 採用新型高效率環保冷媒，不污染環境。

- Exhaust heat is removed from the top.
- Maintain constant cooling temperature that ensures high product precision and reduces wire consumption.
- Intelligent temperature control with precision 0.5°C~1°C.
- It uses temperature control panel and can moving the sensor to install working table.
- Filling the high-efficiency environmental refrigerant is without pollution.

規格表

CR SERIES SPECIFICATION

型式 Model		CR-08S	CR-12S	CR-18S	CR-24S	CR-36S
冷卻能力 Cooling capacity	BTU/HR 50/60Hz	6400/8000	9600/12000	14400/18000	19200/24000	28800/36000
	KCAL/HR 50/60Hz	1600/2000	2400/3000	3600/4500	4800/6000	7200/9000
	W 50/60Hz	1860/2325	2790/3488	4186/5233	5580/6976	8372/10465
使用範圍 Operative range	室溫 Room temperature	5°C ~ 45°C				
	液溫 Liquid temperature	5°C ~ 45°C				
設定範圍 Setting range	差溫控制 Differential temperature controller	-9.9°C ~ 9.9°C				
	定溫控制 Constant temperature controller	20°C ~ 40°C				
電源 Power Source	V	1ø AC220V 50/60Hz			3ø AC220V 50/60Hz	
總負荷電流 Total overburdening current consumption	A	6	7	8	8	10
適用吐油量 Applicable discharge rate	l/min	37/40	37/40	37/40	37/40	37/40
進出口管徑 Inlet and outlet pipe-diameter	inch	3/4"x3/4"	3/4"x3/4"	1"x1"	1"x1"	1"x1"
外型尺寸 Dimension (DxWxH)	mm	475x537x811	475x537x811	696x494x1217	696x494x1217	926x606x1299
冷媒 Refrigerant	gas	R134a/R407C				
總重量 Weight	kg	50	50	100	108	128

CR-□S

- 智慧型溫度控制 Intelligent temperature control
- 冷卻能力 (x1000 BTU/HR) Cooling capacity
- 線切割機專用水冷卻機 Wire cutting machine cooler

• 特殊規格設計及其他電壓需求請與我司聯絡。
We welcome customized design and other voltage requirement.
• 本公司因技術需求或升級有隨時更改內容、文字、產品規格之權利，更改部分恕不另行通知。
We reserve the right of changing the specifications and modification without any notice.